



Feb. 16 1891

I commenced Survey of Section  
9 Town 7 North,

Range 7 West.

E. F. Cox

County Surveyor.

John Beasley } Chainman  
E. John Page }

S. A. Lynn J. B. Sumner

14 No objection to these  
parties acting.

COURSE. DISTANCE. REMARKS.

West.	From N.E. Cor 39.90 1/2	N 1/2	
	79.81	N.W. Cor, Re Est. & Set Parker Corner	3° 15'
South.	" N.W. Cor 39.79	N 1/2	
	78.58	S.W. Cor	
East.	" S.W. Cor 40.03 1/2	S 1/4	
	80.07	S.E. Cor Stone Set & Established	
North.	" Cor 1/4 19.88 1/2	E 1/4 N.W.	
	" Center 1/4		
South	19.92	E 1/4 S.W.	
	" Center 1/4		
West.	19.93	N 1/4 S.W.	
	" Center 1/4		
East.	19.92	N 1/4 S.E.	

Corners Established.	Monument.	Bearing Trees.	Diameter in Inches.	Course.	Links Distant.
Cor No 7 On Plat	Stone	Quaifras	8	North	1
Re Est.		White Oak	9	N 19 1/2 W	2 1/2
Cor " 21 " "	"	" "	17	S 22 W	80
		Black "	12	S 52 W	99
" " 18. " "	"	White "	4	S 71 W	3 1/2
		Burn "	12	S 62 W	154
" " 24 " "	"	Burn Oak	12	S 62 W	151
" " 8 " "	"	Persimmon	4	S 52 W	94
		Well in lot	12	N 85 1/2 W	214
" " 9 " "	"	Stone (Lime)	W	W	50
		" Sand	W	E	50
Re Est 10 " "	Already Set. With Stone				
			5.86	E 16 1/2 Links	
" " 25 " "	" Stone		W	East	50
	"		W	West	50

All Parties were notified 10 days. by written notice. by John Page.

S.W. Cor was determined & established. by running to S.W. Cor Dec 16 & by taking Stone Set out N 1/4 Sec 9. I believe S.E. Corner is located when it formally was.